

arabidopsis

Percival model AR-22L

Chamber shown with optional humidifiers

applications

- Designed for growth of the Arabidopsis plant
- Provides adequate space for growing the plant to maturity under controlled temperature, humidity and light conditions
- Incorporates two individually controlled environments in one compact footprint

Please compare your own requirements to the specifications listed below.

percival's intellus ultra controller

- Controls temperature, lighting, humidity (optional) and CO₂ (optional)
- Single-board electronic solid-state design includes 10 key membrane keypad with LED indicators and vacuum fluorescent display
- Programs can be configured to run in real time or elapsed time
- Ramping and non-ramping program methods available for each programming mode
- Multiple programs can be linked creating complex environmental profiles
- Optional Intellus Web Server allows monitoring and controlling of chamber via web browser (requires Internet Explorer 6.0+) (this option allows for remote monitoring and programming of chamber including alerts and current condition updates for up to five e-mail addresses)

Please refer to www.percival-scientific.com for additional information regarding the control system.

lighting system

- Each tier of shelves is lighted by (8) 17W cool white fluorescent lamps and (2) 25W incandescent lamps properly spaced for uniform light intensity over entire shelf
- Intensity programmable up to 250 $\mu\text{moles}/\text{m}^2/\text{s}$ of light irradiance measured @ 6" from lamps on 3 on/off light events
- Two levels of programming of fluorescent lighting and one level of programming of incandescent lighting
- Programming and control of the lighting is done via Intellus real time controller



airflow/circulation

- Conditioned air circulates through a rear wall plenum, and travels horizontally across each shelf (air then flows vertically upward through the space between the door and shelves back to the unit cooler)

cabinet construction

- Interior constructed of 22-gauge electro-zinc plated steel
- Exterior constructed of 18-gauge exterior electro-zinc plated steel
- Welded seams and joints on outer and inner shells
- Inner shell supported by non-compressing/non-thermal conducting material locking inner liner in place without a metal-to-metal bond to outer case
- Chamber is completely self-contained
- Overall wall thickness is 2" (5.1 cm)
- Two 1 1/4" diameter access ports on R.H. wall (one per compartment)
- Stainless steel chamber floor equipped with floor drain and hose assembly
- Contains caster assembly and adjustable leveling legs to compensate for floor unevenness in the lab

AR-22L specifications (subject to change without notice)

Temp Range with all lights on	Interior Space volume		Total Shelving Floor Area		Maximum Growing Height		Exterior Dimensions						Light Intensity 6" from lamps unless otherwise noted	Tiers	
	°C	ft ³	m ³	ft ²	m ²	in	cm	width		depth		height			
10-44±0.7	29.1	0.8	10.8	1	20	50.8	33.5	85.1	36.6	93	77.9	197.8	250	2	

arabidopsis Percival model AR-22L

insulation

Woodless construction using CFC free insulation (overall wall thickness is 2" [5.1 cm], ample insulation for maintenance of stated temperature range)

doors

- Two doors each with an opening of 29.2" x 27.5" (74 cm x 70 cm) providing full access to chamber interior (magnetic gasket provides a tight seal to door frame)

interior space

- 29.1 ft³ (0.8 m³) with work area of 10.8 ft² (1 m²) provided on two shelves

shelving

- One tier per compartment of white epoxy coated steel wire shelving (each shelf is 27" D x 28.8" W [68.6 cm x 73 cm])
- Shelves are supported by shelf clips allowing ½" vertical adjustments (maximum growing height is 20" [50.8 cm])

finish

- Interior and exterior painted with highly reflective, environmentally friendly, high temperature baked white powder coating

refrigeration

- Twin condensing unit (this continuous running condensing unit ensures precise temperature control by alternately cycling refrigerant and hot gas to coil; this also prolongs life of compressor, and eliminates risk of ice build up in coil)
- Solenoid valves have extended stem for quiet and long life operation
- Ceiling mounted evaporator coils incorporate dual air circulation fans in aluminum housing (heat rejection to ambient [standard chamber] = 6000 BTU/hr.)

temperature range

- 10°-44°C (±0.7°C) lights on and 2°-44°C (±0.7°C) lights off

temperature safety limit controls

- (Experiment Protection) Adjustable high and low temperature controls, audible alarms, and visual indicators provided
- Controls shut down all power to the chamber, activating alarms (when the temperature returns to the normal range the system will automatically reset)

humidity control (optional)

- Additive humidity control of higher than ambient to 65% (±10%) lights on for set temperatures between 20° to 30°C
- Humidity control of higher than ambient to 90% (±10%) lights off for set temperatures between 15° to 30°C
- Extended humidity ranges available
See other specification sheets or consult factory for additional information.

options (most popular)

- Intellus Ultra Web Server (C9)
- Communications Software (C9+)
- Intellus Ultra with Touchscreen and Internet capabilities (C10)
- Ultrasonic Humidifier with advanced RH Sensor (H11)
- Dehumidification via independent dehumidifying coil with reheat heaters and Ultrasonic Humidifier (H12)
- Ultrasonic Humidifier with Electronic RH sensor (H14)
- CO₂ enrichment package
- Door with observation window and cover (Q2)
- Door with fresh air ports (Q1)
- Self-contained water-cooled condensing unit
- Dry alarm contacts
- Dimmable lighting (closed loop with PAR light sensor) (Q22)
- Dimmable lighting (open loop control) (Q23)
- Extended temperature ranges available
See other catalog sheets or consult factory for additional accessories.

convenience receptacles

- One 115/1/60 convenience receptacle provided inside each each compartment

electrical service requirements

- 115/1/60 - 23 amps (load is split between two power cords)
- One power cord and grounded plug provided for each chamber section (2 total)
Consult factory for electrical services when adding accessories to the chamber



Donauwörther Str. 9
86637 Wertingen
Tel.: +49 (0) 8272 6430 60
Fax: +49 (0) 8272 6430 61

info@plantclimatics.de
www.plantclimatics.de